



High professional hydraulic/pneumatic blind riveting tool with extraction and multifunction trigger made for heavy industry use.

Multifunctional Trigger

Enables to control the suction through a trigger button; when the trigger is pushed and shifted up – the suction is deactivated, when pushed and shifted down – the suction is activated.

Revolving Air Supply

Enables manipulation with an air supply hose pipe which does not restrain the operator from riveting in any position.

Ergonomics and Design

AirPower series riveters are distinguished from other products by the timeless design of Prof. Pavel Škarka and sophisticated ergonomy, which allows their easy set up and use in demanding condition of series production.

Multifunctional Mandrel Collector

Enables to control the vacuum system.

Position 0 = the suction is deactivated and the mandrel collector can be removed and emptied.

Position 1 = the suction is deactivated and the tool is ready to work, the rest of mandrels will be removed manually by tilting the tool.

Position 2 = the suction is activated and the tool is ready to work, the rest of mandrels will be transported into the mandrel collector automatically.

Ø	ALUMINIUM	STEEL	STAINLESS STEEL
2.4	●	●	●
3.0	●	●	●
3.2	●	●	●
4.0	●	●	●
4.8 / 5.0	●	●	●

SPECIFICATIONS	
Capacity	2,4-4,8mm Al, St, Rv
Weight	1.25 kg
Dimensions	272mm x 264mm x 99mm
Stroke	17mm
Pressure required	5-7 Bar
Traction power (6 bar)	7.3kN
Equipment	Nose pieces 3,0-4,8mm

* 2.4 End pieces can be added as required