

HUCK 3585 HYDRAULIC RIVET TOOL



The Huck 3585 Air Blind Rivet Tool operates at 7400 psi (510 BAR) PULL and 3200 psi (220 BAR) RETURN pressures supplied by 918 Powerig hydraulic power unit models or equivalent. Lengths and weights do not include Nose Assemblies. Except for the nose assembly, the hydraulic rivet gun is ready to be attached to a HUCK POWERIG with handle, hoses, couplers and control cable. The Huck 3585 tool is basically a cylinder and piston assembly. A relief valve, designed to relieve hydraulic pressure at both ends of the stroke, is positioned next to the piston.

Weight : 8.62 kg

Maximum Operating Temperature : (51,7° C)

Power Source : Powerig Hydraulic Unit

Stroke : 46 mm

Max. Pulling Pressure : 510Bar

Head Length: 219 mm

Head Width: 48 mm

Total Height: 164 mm

Length : 22 cm

C50L / BOBTAIL / BOM rivets are applicable.

Nose assemblies, hydraulic power equipment, hose assembly and nose ends are sold separately.

HUCK 3585 NOZZLE CODES AND DIAMETERS

C50L

99-5008	-	15.8
99-5009	-	15.8
99-5010	-	19.0
99-5011	-	9.5
99-5013	-	38.0
99-5021	-	12.7

BOBTAIL

99-7830	-	M12
99-7830CC	-	M12
99-7830CX	-	M12
99-7831	-	M16
99-7831CC	-	M16
99-7831CX	-	M16
99-7832	-	M20
99-7832CC	-	M20
99-7832CX	-	M20
99-7834	-	M14
99-7834CC	-	M14
99-7834CX	-	M14
99-7835	-	M12
99-7835CC	-	M12
99-7835CX	-	M12
99-7836	-	M19
99-7836CC	-	M19

BOM

99-5102	-	15.8
99-5103	-	19.0

