

HUCK 256 PNEUMATIC INSTALLATION TOOL



Powered by compressed air, Huck pneumatic tool systems provide efficient installation of Huck Lock Bolts and blind rivets up to 9.5 mm in diameter. Known for their reliability and robust performance, Huck pneumatic tools are specially designed to ensure consistent and precise assembly. This consistency ensures reliable Huck Lock bolts and blind fastener installations every time, guaranteeing the performance and integrity of your joint.

Weight 5 Kg

Air Pressure: 6.20 bar

Tensile Capacity: 44.42kN at 6.2 bar

Stroke : 22.23mm

Noise Level : 85dB(A)

Operating Temperature: 0 to 51.7°

Height : 37 cm

Length : 22.5 cm

Coated piston rods extend seal life and contribute to durability.

Huck Lok - Magna-Lok - Auto Bulb - Boom - C6L - Magna Grip rivets can be applied.

Nozzle parts sold separately.

HUCK 256 NOZZLE CODES AND DIAMETERS

BOM

99-1314	-	6.4
99-1272	-	9.5
99-1053	-	4.8
99-830-1	-	6.4
99-769-2	-	7.9
99-769	-	7.9

MAGNA-LOK / HUCK-LOK/ MAGNA-BULB / AUTO BULB

99-1488	-	6.4
99-3327	-	4.8
99-3328	-	6.4

MAGNA-LOK

99-3318	-	9.5
99-3329	-	9.5

C6L

99-100	-	9.5
99-100-1D2	-	9.5
99-100-245	-	9.5
99-100-2D2	-	9.5
99-100-3D2	-	9.5
99FD-100-D2	-	9.5
99-2558	-	4.8
99-2564	-	6.4
99-99	-	7.9

MAGNA-GRIP

99-1276	-	4.8
99-1290	-	6.4
99-1439	-	7.9
99-1440	-	9.5
99-1450	-	9.5
99-1450-2	-	9.5
99-3206	-	4.8
99-3207	-	6.4
99-MGE-12-IRAG	-	9.5

MAGNA-BULB

99-3307	-	7.9
---------	---	-----

HUCKTAINER

99-3438	-	9.5
---------	---	-----