






Pre-Assembled Panel Fasteners

Series CPFC2



CPFC2 panel fasteners provide permanent attachment of screw assemblies to removable sheet metal panels. Pre-assembled screw assemblies remain captive for easy mounting and removal of panel.

Series	Material	Finish
CPFC2	300 Series Stainless Steel	Passivated ASTM A967



Thread: External 2A, ANSI B1.1 (6g, ANSI/ASME B1.13M).
Use in: Materials with Rockwell Hardness B-70 or less.



Min. Panel Thickness
.060 in. (1.5mm)

Part Number Structure:


CPFC2 440-40



Dimensions & Specifications

Thread Size	Part Number	G ±.016	P ±.016	L ±.016	D +.016 -.010	A Max.	Y ±.005	B ±.010	C Max.	 +.003 -.000	 Min.
#4-40	CPFC2440-40	.250	.000	.19	.312	.36	.072	.28	.264	.265	.25
	CPFC2440-62	.375	.125								
	CPFC2440-84	.500	.250								
#6-32	CPFC2632-40	.250	.000	.19	.344	.36	.072	.28	.280	.281	.28
	CPFC2632-62	.375	.125								
	CPFC2632-84	.500	.250								
#8-32	CPFC2832-50	.312	.000	.25	.375	.45	.082	.36	.311	.312	.31
	CPFC2832-72	.437	.125								
	CPFC2832-94	.562	.250								
#10-32	CPFC21032-50	.312	.000	.25	.406	.45	.082	.36	.343	.344	.34
	CPFC21032-72	.437	.125								
	CPFC21032-94	.562	.250								
1/4-20	CPFC2420-60	.375	.000	.31	.468	.58	.097	.47	.412	.413	.38
	CPFC2420-82	.500	.125								
	CPFC2420-04	.625	.250								

Continued on next page.



Pre-Assembled Panel Fasteners

Series CPFC2



Continued from previous page.

Dimensions & Specifications

Thread Size	Part Number	G ±.4	P ±.4	L ±.4	D +.4 -.25	A Max.	Y ±.13	B ±.25	C Max.		
										+ .08 - .00	Min.
M3 x 0.5	CPFC2M3-40	6.4	.0	4.8	7.92	9.14	1.83	7.2	6.71	6.73	6.35
	CPFC2M3-62	9.5	3.2								
	CPFC2M3-84	12.7	6.4								
M4 x 0.7	CPFC2M4-50	7.9	.0	6.4	9.53	11.43	2.08	9.3	7.9	7.92	7.87
	CPFC2M4-72	11.1	3.2								
	CPFC2M4-94	14.3	6.4								
M5 x 0.8	CPFC2M5-50	7.9	.0	6.4	10.31	11.47	2.08	9.3	8.72	8.74	8.63
	CPFC2M5-72	11.1	3.2								
	CPFC2M5-94	14.3	6.4								
M6 x 1.0	CPFC2M6-60	9.5	.0	7.9	11.89	14.73	2.46	12.0	10.47	10.49	9.65
	CPFC2M6-82	12.7	3.2								
	CPFC2M6-04	15.9	6.4								

Installation & Performance Data

Thread Size	Cold-rolled Steel		5052-H34 Aluminum		
	 Installation Force (lbs.)	 Pushout (lbs.)	 Installation Force (lbs.)	 Pushout (lbs.)	
INCH (in.)	#4-40	3000	300	2400	240
	#6-32	3500	350	2700	275
	#8-32	3800	400	2900	300
	#10-32	4000	500	3000	400
	1/4-20	5000	600	3500	400
	(kN)	(N)	(kN)	(N)	
METRIC (mm)	M3	13.3	1334	10.7	1068
	M4	16.9	1779	12.9	1334
	M5	17.8	2224	13.3	1779
	M6	22.2	2669	15.6	1779